Seat Belt for Forklift

Forklift Seat Belts - This guideline reason is to be able to explain the Regulation requirements for the application of operator restraints or seatbelts on forklifts. It is the employers' liability to be able to make certain that each and every machine, piece of equipment and tool within the workplace is chosen and used correctly and operated according to the manufacturer's directions.

Rough Terrain lift trucks ought to meet the regulations of ANSI Standard ASME B56.6-1992 regarding their design, maintenance, inspection, fabrication and use.

Side boom tractors and mobile machine together with a Rollover Protective Structure, or ROPS for short, should contain seat belts that satisfy the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whichever mobile equipment has seat belts required by law, the operator and subsequent passengers ought to make certain they utilize the belts every time the vehicle is in motion or engaged in operation as this can cause the machinery to become unstable and thus, unsafe.

When a seat belt or various driver restraint is needed on a forklift.

While operating a lift truck, the seat belt requirements will depend on several factors. Contributing factors to this determination might include whether or not the the forklift is outfitted together with a Rollover Protective Structure, the kind of forklift itself and the year the lift truck was manufactured. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to an operator restraint device, enclosure or system, ANSI Standard ASME B56.1-1993 in the case of powered industrial trucks, is designed to help the driver in reducing the chance of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The restraint device or system might include a seat belt, while a seat belt is not necessarily a part of such machine or system.